



Stronger Bonds, Better Life

SEAL IN THE WET

Description

Bostik Seal In the Wet® is an enhanced hybrid modified polymer formulation that gives an instant seal when applied, where others fail. One of the strongest sealants on the market, it bonds to most surfaces with a virtually unbreakable grip that is able to withstand shock and vibration.

Classifications

- Suitable for drinking water applications (AS/NZS 4020:2005)

Features

- Seals leaks immediately
- Seals under water
- Seals in the rain
- Suitable for water potable applications
- Bonds & seals to most surfaces, including wet surfaces
- High bond strength
- Non corrosive to metals
- Waterproof & UV resistant
- Environmentally friendly, Low VOC
- Elasticity ($\pm 15\%$)
- Paintable #



Recommended Uses

- Sealing around roofs and gutters
- Bathrooms & wet areas
- Sealing joints between concrete & brick
- Sealing windows
- Interior and exterior applications

Coverage

- Approximately 10 linear metres of 6mm bead x 5mm depth from a 290ml cartridge.

Application Instructions

Surfaces must be clean and free from dust and grease. Recommendations are for guidance only, since conditions of use are completely beyond our control.

PROPERTIES

Colour	Translucent / Grey
Tooling/Skin Time @ 20°C	15-30 Minutes Approximately
Tack Free Time @ 20°C (ASTM C-679)	120 Minutes Approximately
Cure Time (To 3mm depth @ 23°C & 50% RH)	24 Hours
Application Range	+ 5°C to +40°C
Performance Range	- 40°C to +100°C
Hardness Shore A (ASTM D-2240)	45 Trans / 55 Grey (23°C, 50% RH)
Tensile Strength (ASTM D-412)	3.5 N/mm ²
Sag, Slump	0
Specific Gravity	1.1 Approximately - Trans 1.5 Approximately - Grey
Elasticity	± 15%

#Lightly buff Seal In The Wet with fine sand paper once fully cured, before applying any paint or coating.

PRODUCT DETAILS

ITEM NO	ITEM NAME	SIZE	COLOUR	PACK QTY
372706	SEAL IN THE WET	290ml	Grey	12
372692	SEAL IN THE WET	290ml	Translucent	12

Important Notes: This sell sheet is not intended as a replacement for the appropriate Technical Data Sheet. Always check the Packaging, Technical Data Sheet and MSDS before using. If there is any doubt contact Bostik before commencing work.



SEAL IN THE WET - GREY

Scan QR code to download
MSDS , TDS.



SEAL IN THE WET - TRANS

Scan QR code to download
MSDS , TDS.



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au