

AIRFLO AND WHISPERAIR *BLOWERS*

Whisper quiet performance

Enjoy the soothing effects of powerful, invigorating bubbles in your spa without excess equipment noise.

- Whisper quiet operation
- Hi-flow air movement
- Compact design
- Variable mounts



Compact Design

The compact design of Waterco's spa blowers enables installation in smaller areas and tight corners. The convenient position of the mounting base and air inlet/outlets reduces installation time and cost.

Thermal Cutout

Waterco spa blowers feature an important safety feature, an integral thermal cutout. This cutout stops the electric motor from becoming excessively warm. This cutout does not require manual resetting and will automatically restart the motor when it has sufficiently cooled.

Standard Model – Airflo, Whisperair, Whisperair S

The standard model of the blower draws air into the unit through the bottom cowl of the blower.

The airflo version has air inlet holes throughout the bottom cowl, while the Whisperair models draw all the required air in through gaps around the perimeter of the bottom cowl.



Air switch Models (Whisperair S and Whisperair S Elite)

The Whisperair S comes with an air switch controller and connecting tubing to provide remote activation / deactivation of the blower. The button for the air switch controller is designed to be installed in the shell of the spa and is connected to the blower via tubing.



Variable mounts

All Waterco Blower's have two identical 50mm diameter outlet ports. One of the ports is in the bottom cowl of the blower and the other is in the side of the blower. The stand can be attached to either of these ports and leaves the other free to connect to the spa via the piping. It is also possible to connect the pipe to the outlet port in the bottom cowl of the blower and seal off the other outlet port.



Technical Data

Product Description	Power (Watts)	Amps (A)	Max. Operating Pressure (kPa)	Max. Flow Rate (lt /sec)	Max. Operating Noise (dBa)	Voltage (V)	Cycle (Hz)	Unit Weight (kg)	Electrical Protection Rating	Inlet / Outlet Ports (mm)
Airflo Spa Blower	900	4.0	17	72	91.6	220-240	50	5	IP23	50
Whisperair Spa Blower	900	4.0	17	72	91.0	220-240	50	5	IP23	50
Whisperair Spa Blower with Air Switch	900	4.0	17	72	91.0	220-240	50	5	IP23	50
Airflo Spa Blower	1200	5.8	27	72	94.6	220-240	50	5	IP23	50
Whisperair Spa Blower	1200	5.8	27	72	94.0	220-240	50	5	IP23	50
Whisperair Spa Blower with Air Switch	1200	5.8	27	72	94.0	220-240	50	5	IP23	50

Warranty

Waterco blowers are covered by a comprehensive 12 month warranty.

Note: Waterco 900/1200 watt blowers are designed for domestic use, only. They operate with a heat switch that will automatically cut out @ 900 watt / 125° & 1200 watt / 165°. Good ventilation is recommended to help maintain good air flow and temperature control.



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au