
ELECTRICAL DATA

- DRIVE CURRENT: 1.0A
- O VOLTAGE: 12V ac
- **─ WATTAGE:**12w
- **OUTPUT:** 180lm (typical)
- LUMINOUS EFFICACY: 15lm/w
- DIMMABLE: trailing or leading edge compatible
- SURGE PROTECTION: 4 joules (2ms)
- □ LUMENS MAINTENANCE: 70% @ 50,000hrs




PHOTOMETRIC DATA


POLAR PLOT


- RELATIVE INTENSITY
 - +/-80°:38%
 - +/-60°:60%
 - +/-45°:75%

 - +/-20°:95% +/- 0°:100%









NOTE: ALL LIGHTS HAVE BEEN TESTED IN AIR AND THE VISUAL APPEARANCE IN WATER WILL VARY DEPENDING ON COLOUR, WATER ATTENUATION, POOL INTERIOR COLOUR ABSORBSION AND WATER CLARITY. SPA ELECTRICS RESERVES THE RIGHT TO CHANGE THESE SPECIFICATIONS WITHOUT PRIOR NOTICE



POOL PRODUCTS Quality Pool & Spa Products

Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122 Telephone STD 61-7-3849 5385


Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au Web: www.rainbowpoolproducts.com.au



ELECTRICAL DATA

- DRIVE CURRENT: 1.0A
- VOLTAGE: 12V ac
- **─ WATTAGE:**12w
- OUTPUT: 850lm (typical)
- LUMINOUS EFFICACY: 71lm/w
- DIMMABLE: trailing or leading edge compatible
- SURGE PROTECTION: 4 joules (2ms)
- □ LUMENS MAINTENANCE: 70% @ 50,000hrs



PHOTOMETRIC DATA


POLAR PLOT


- **RELATIVE INTENSITY**
 - +/-80°:38% +/-60°:60%

 - +/-45°:75%
 - +/-20°:95% +/- 0°:100%

WAVELENGTH

- O DOMINANT: 570nm
- **□ PEAK:** 580nm









- → CCT: 3800k - COLOUR
- **PURITY:** 30% CIEx: 0.39
- CRI. (Ra):71 CIEy: 0.38

NOTE: ALL LIGHTS HAVE BEEN TESTED IN AIR AND THE VISUAL APPEARANCE IN WATER WILL VARY DEPENDING ON COLOUR, WATER ATTENUATION, POOL INTERIOR COLOUR ABSORBSION AND WATER CLARITY. SPA ELECTRICS RESERVES THE RIGHT TO CHANGE THESE SPECIFICATIONS WITHOUT PRIOR NOTICE





Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122 Telephone STD 61-7-3849 5385


Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au Web: www.rainbowpoolproducts.com.au



ELECTRICAL DATA

- **DRIVE CURRENT: 1.0A**
- VOLTAGE: 12V ac **─ WATTAGE:**12w
- OUTPUT: 500lm (typical)
- LUMINOUS EFFICACY: 41lm/w
- DIMMABLE: trailing or leading edge compatible
- SURGE PROTECTION: 4 joules (2ms)
- □ LUMENS MAINTENANCE: 70% @ 50,000hrs




PHOTOMETRIC DATA


POLAR PLOT


- **RELATIVE INTENSITY**
 - +/-80°:38%
 - +/-60°:60%
 - +/-45°:75% +/-20°:95%

 - +/- 0°:100%









NOTE: ALL LIGHTS HAVE BEEN TESTED IN AIR AND THE VISUAL APPEARANCE IN WATER WILL VARY DEPENDING ON COLOUR, WATER ATTENUATION, POOL INTERIOR COLOUR ABSORBSION AND WATER CLARITY. SPA ELECTRICS RESERVES THE RIGHT TO CHANGE THESE SPECIFICATIONS WITHOUT PRIOR NOTICE.





Rainbow Pool Products


PO Box 2388, Mansfield Qld 4122 Telephone STD 61-7-3849 5385 Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au Web: www.rainbowpoolproducts.com.au



ELECTRICAL DATA


- DRIVE CURRENT: 1.0A
- O VOLTAGE: 12V ac
- **── WATTAGE:**12w
- OUTPUT: RED:240lm GREEN:500lm BLUE:180lm
- **LUMINOUS EFFICACY:** R:20 lmw G:41lmw B: 15lmw
- DIMMABLE: Not compatible with this model.
- **SURGE PROTECTION:** 4 joules (2ms)
- LUMENS MAINTENANCE: 70% @ 50,000hrs



PHOTOMETRIC DATA


POLAR PLOT

- RELATIVE INTENSITY
 - +/-80°:38%
 - +/-60°:60%
 - +/-45°:75%
 - +/-20°:95%
 - +/- 0°:100%





- RED
- **DOMINANT:** 627nm
- **─ PEAK:** 645nm
- GREEN
- **DOMINANT:** 512nm
- **─○ PEAK:** 512nm
 - BLUF
- ODMINANT: 466nm
- **□ PEAK:** 470nm



NOTE: ALL LIGHTS HAVE BEEN TESTED IN AIR AND THE VISUAL APPEARANCE IN WATER WILL VARY DEPENDING ON COLOUR, WATER ATTENUATION, POOL INTERIOR COLOUR ABSORBSION AND WATER CLARITY. SPA ELECTRICS RESERVES THE RIGHT TO CHANGE THESE SPECIFICATIONS WITHOUT PRIOR NOTICE.





Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122 Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au Web: www.rainbowpoolproducts.com.au

