



- Large hexagonal shaft transmits power without wear or flex
- Heavy gauge outer shell makes it strong, rigid and long lasting
- Superior ceramic wear surface reduces problems running in sandy or abrasive water
- Floating impeller design reduces sand lock up problems and ensures a longer motor life and trouble free operation

Applications:

• Residential, irrigation, water transfer and stock watering.

| | 20 Litre pump | | | | |
|---|---------------|------|--------|--|--|
| The 20 litre pump range are manufactured to a special TRIMLINE OD of 3.75" and features bronze ends for corrosion protection. Discharge 1 1/4" BSP. | | | | | |
| MODEL | HP | kW | Stages | | |
| 20S4FTL | 1.5 | 1.10 | 26 | | |
| 20S4ETL | 1.0 | 0.75 | 22 | | |
| 20S4DTL | 0.75 | 0.55 | 15 | | |
| 20S4CTL | 0.5 | 0.37 | 11 | | |
| 30 Litre pump | | | | | |
| Glass reinforced engineering plastic ends for corrosion protection. Discharge 1 1/4" BSP. | | | | | |
| MODEL | HP | kW | Stages | | |
| 30S4GT | 2.0 | 1.5 | 25 | | |
| 30S4FT | 1.5 | 1.1 | 19 | | |
| 30S4ET | 1.0 | 0.75 | 14 | | |
| 30S4DT | 0.75 | 0.55 | 11 | | |
| 50 Litre pump | | | | | |
| Glass reinforced engineering plastic ends for corrosion protection. Discharge 1 1/4" BSP. | | | | | |
| MODEL | НР | kW | Stages | | |
| 50S4GT | 2.0 | 1.5 | 22 | | |
| 50S4FT | 1.5 | 1.1 | 17 | | |
| 50S4ET | 1.0 | 0.75 | 12 | | |
| | | | | | |



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122 Telephone STD 61-7-3849 5385 Facsimile STD 61-7-3849 5384

Web: www.rainbowpoolproducts.com.au

| 70 Litre pump | | | | | |
|--|-----|------|--------|--|--|
| Glass reinforced engineering plastic ends for corrosion protection. | | | | | |
| Discharge 1 1/4" BSP. | | | | | |
| MODEL | HP | kW | Stages | | |
| 70S4HT | 3.0 | 2.2 | 26 | | |
| 70S4GT | 2.0 | 1.5 | 17 | | |
| 70S4FT | 1.5 | 1.1 | 13 | | |
| 70S4ET | 1.0 | 0.75 | 10 | | |
| 90 Litre pump | | | | | |
| Glass reinforced engineering plastic ends for corrosion protection. Discharge 1 1/4" BSP. | | | | | |
| MODEL | HP | kW | Stages | | |
| 90S4HT | 3.0 | 2.2 | 18 | | |
| 90S4GT | 2.0 | 1.5 | 12 | | |
| 90S4FT | 1.5 | 1.1 | 10 | | |
| 150 Litre pump | | | | | |
| Glass reinforced engineering plastic ends for corrosion protection. Discharge 1 1/4" BSP. | | | | | |
| MODEL | HP | kW | Stages | | |
| 150S4KT | 7.5 | 5.5 | 30 | | |
| 150S4JT | 5.0 | 3.7 | 20 | | |
| | | | | | |







