

Triton® II

Fiberglass Sand Filter



The #1 sand filter in the world

Triton® II is the result of over 40 years of product evolution and refinement. It has set the industry standard for effectiveness, efficiency, long runs between service, and providing years of dependable, low maintenance operation.

Triton II features a special internal design that keeps the sand bed level, ensuring even water flow, and resulting in the most efficient filtration possible

- Time-proven internal design ensures that all water receives maximum filtration for crystal clear results.
- GlasLok™ process creates a one-piece, fiberglass reinforced tank with a UV-resistant coating for years of dependable, corrosion-resistant service.
- Flow system design controls filtration quality and ensures maximum run times between backwashing to save you time.



Triton® II

Fiberglass Sand Filter

Easy access, heavy-duty closure with built-in pressure relief valve makes inspection and maintenance fast, safe, and easy

Threaded bulkhead connectors for easy installation and service

GlasLok™ process creates a one-piece, fiberglass reinforced tank with UV-resistant surface finish for years of unequal strength and durability



Model Number	Filter Area Sq. Mt.	Vertical Clearance	Filter Diameter	Required Sand† (kgs)	Flow Rate LPM		Turnover Capacity-Res. (Litres)		
					Res.	Com.	8hrs.	10hrs.	12hrs.
TR 40	0.178	826mm	483mm	80	144	144	69,045	86,307	103,568
TR 50	0.228	934mm	533mm	103	186	186	89,032	111,291	133,549
TR 60	0.291	953mm	609mm	148	239	239	114,470	143,088	171,706
TR 100	0.456	1061mm	762mm	273	371	281	178,065	222,582	267,098
TR 140	0.655	1200mm	914mm	420	534	402	256,196	320,245	384,295

† Use standard 16/30 silica sand.

Required clearance to remove the closure.

** Maximum flow rate. Flow rate is based on 287 lts per sq.mt. of filter area. Actual system flow will depend on plumbing size and other system components.

The best reputation in the industry for all the right reasons

Besides its superior filtration performance, Triton® II delivers a level of dependability and ease of operation and maintenance for a track record that's unsurpassed. Every design detail has been refined to make Triton II the industry standard. Additional features include :

- Combination sand and water drain speeds servicing and winterizing.
- All internal parts are threaded for ease of maintenance.
- Swing-away water diffuser allows instant access to sand and all internal parts.
- Ten-year limited warranty. See warranty for details.



Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: info@rainbowpoolproducts.com.au

Web: www.rainbowpoolproducts.com.au