

# Waterco FPI Valves

Engineered for optimal performance



Waterco FPI Valves are designed for optimal hydraulic flow and engineered to be maintenance free.

- Teflon™ seals\*
- Quick installation
- UPVC and ABS construction
- Available in 2 and 3 way configurations
- 316 grade stainless steel components
- Up to 600 kPa pressure rated



## Waterco FPI Valves

### Teflon seals\*

Teflon™ seals offer minimal friction and smooth operation.

### Quick installation

The FPI valve body is made from UPVC. Its compatibility with PVC pipes will ensure quick setting and a stronger bond.

### Engineered strength

Both the FPI Valve lid and handle are constructed from premium ABS plastic. The valve's steel components are constructed from high quality 316 grade stainless steel.

### High pressure rating

Its advanced design and construction enable the FPI valves to withstand a working pressure of 400 to 600 kPa depending on the model selected.

### Optional half unions

25/32mm and 65/80mm valves are available with the option of half unions for ease of installation and maintenance.

### Warranty

FPI valves are covered by a 12 month warranty against faulty materials and workmanship.



2 way 40/50mm slip fit valve



3 way 40/50mm slip fit valve



3 way 25/32mm slip fit valve



3 way 25/32mm valve threaded with half unions.



2 way 50/65mm slip fit valve



3 way 50/65mm slip fit valve

### Specifications

Product Code	Description	Nominal Size	Teflon Seals	Pressure Rating
148503	2 way valve threaded with half unions	25/32 mm	✓	600 kPa
148505	2 way valve slip fit	25/32 mm	✓	600 kPa
148500	3 way valve threaded with half unions	25/32 mm	✓	600 kPa
148502	3 way valve slip fit	25/32 mm	✓	600 kPa
14852	2 way valve slip fit	40/50 mm	✓	400 kPa
14853	3 way valve slip fit	40/50 mm	✓	400 kPa
14856	2 way valve slip fit	50/65 mm	✓	400 kPa
14860	3 way valve 360° slip fit	50/65 mm	✓	400 kPa
14882	2 way valve slip fit	65/80 mm	✓	400 kPa
14892	2 way valve threaded with half unions	65/80 mm	✓	400 kPa
14883	3 way valve slip fit	65/80 mm	✓	400 kPa
14893	3 way valve threaded with half unions	65/80 mm	✓	400 kPa
148564	2 Way Valve Actuated Type (4 Bar)	50/65mm	✓	400 kPa
148584	3 Way Valve Actuated Type (4 Bar)	50/65mm	✓	400 kPa

\*™ Teflon is a Registered Trade Mark of DuPont Corporation



## Rainbow Pool Products

PO Box 2388, Mansfield Qld 4122

Telephone STD 61-7-3849 5385

Facsimile STD 61-7-3849 5384

Email: [info@rainbowpoolproducts.com.au](mailto:info@rainbowpoolproducts.com.au)

Web: [www.rainbowpoolproducts.com.au](http://www.rainbowpoolproducts.com.au)